

Swaltex® Expert Pro lining

Wide lining for **Swaltex®** cold stretched ceilings

Applications

Stretched ceiling lining,
without joins or seams up
to 5m05 wide.



Samples on demand



Resists the propagation
of fire



Certificate on request



Complies with European
security standards



UV digital printing

Wide, coated Trevira fibre sheeting.

Fit using SWAL® Clip Profiles (all references).

European standard EN14716 for stretched ceilings,
requirements and test methods.

- Eco-friendly sheeting
- Ultra-resistant and rot-proof, damp-proof
- Does not fray
- Can integrate all types of technical elements (spotlights, lighting, ventilation etc.)
- Can be painted (acrylic paint)
- Can be printed (UV technique)
- A micro-perforated acoustic version is also available (SWALTex® Acoustic MHF)

TECHNICAL SPECIFICATONS

Weight/Density: 245 g/sq.m

Thickness: 0.44 mm.

PIECE SIZES

Width available:

Gross 3m20 - 3m10 net used (ref. Expert Pro 300)

Gross 4m20 - 4m10 net used (ref. Expert Pro 400)

Gross 5m10 - 5m05 net used (ref. Expert Pro 500)

COLOURS

Optical white

Natural White (off white).

FIRE PROTECTION CLASS

Euroclasse Bs2d0, M1 (certificate on request).

PARTICULARS

Damp-proof (can be used in bathrooms) Heat-resistant.

FITTING METHODS

With *ClipSwal®* CSW 200 et CSW 201 profile clips (CSW 200 and CSW 201) and **Swaltex®** special PVC spatula.

SPECIAL USAGE

For ceilings with join(s), use SWAL® OSW 202 clips. We recommend posing it all in the same direction.

PACKAGING

Cut to order.